



LADLES AND RECEIVERS

1 Cover:

- CALDE® CAST F 65 with CALDE® ANCHORING SYSTEM on top of CERAMIC FIBRES and CALDE® GUN MW STRONG LITE

2 Insulation:

- CERAMIC FIBRES or MICA, at larger vessels behind bricks or CALDE® GUN MW STRONG LITE, secured by bricks or CALDE® GUN M32

3 Hot face:


- CALDE® CAST UB, CALDE® CAST LB 84 G10 as standard solutions
- CALDE® CAST NB 82 QD as quick-drying castable
- CALDE® CAST LX 58 MD as temperature shock resistant alternative, also available as sol-based CALDE® SOL CAST M 60 2CP
- CALDE® RAM PF 55 as ramming option
- CALDE® FLOW AZ as self-flowing option
- CALDE® MIX FLASH A 55 as exothermic DVM option for instant use

4 Repair:

- CALDE® STIX 151 (as best-seller solution)
- CALDE® GUN B 55 M G3 or CALDE® PATCH PF 60 U (for special application)

5 Special components:

- READY-SHAPE solutions for converter plates, purging plugs etc.





EQUIPMENT SPECIFICATIONS

Product name	Grain Size	Temp Limit	Yield (kg / dm ³)	Al ₂ O ₃	SiO ₂	SiC
CALDE® CAST F 65	6mm	1460	2.30	64	30	
CALDE® GUN MW STRONG LITE	4mm	1320	1.60	39	40	
CALDE® GUN M 32	3mm	1650	2.80	89	13	
CALDE® CAST UB	6mm	1680	2.85	85	12	
CALDE® CAST LB 84 G10	10mm	1600	2.85	83	10	
CALDE® CAST NB 82 QD	6mm	1650	2.75	82	14	
CALDE® CAST LX 58 MD	6mm	1650	2.50	57	38	
CALDE® SOL CAST M 60 2CP	6mm	1650	2.50	60	37	
CALDE® RAM PF 55	6mm	1620	2.55	60	35	
CALDE® FLOW AZ	6mm	1650	2.75	59	28	
CALDE® MIX FLASH A 55	3mm	1650	2.10	54	37	
CALDE® STIX 151 Trowelled	6mm	1550	2.10	55	32	
CALDE® STIX 151 Gunned	6mm	1550	2.45	55	32	
CALDE® GUN B 55 M G3	3mm	1500	2.50	53	18	
CALDE® PATCH PF 60 U	5mm	1600	2.20	59	35	

DISCLAIMER: CALDERYS does not warrant the accuracy, fitness for purpose or update of any information disclosed herein. The recipient shall refer to the present content as indicative only. For any instructions or advice, please address formal request to CALDERYS. This document and the information contained herein are the exclusive property of CALDERYS. Reproduction, alteration, copy, release, publication or distribution, in whole or in part, is not allowed. References, trademarks and specifications of the products may vary according to the geographical area to be supplied. For any inquiries regarding supply of products, please liaise with CALDERYS nearest sales contact. Errors and omissions excepted.